

Job Number:
Date:

Project Name:
Splice Count: 0

Project Manager:
Technicians:

Location A:
Location B:

Cable Type:
Connector type:

Strand Count:
Length (ft): 400

Length (M): 121.9

	Wavelength	Cable Loss	Connector Loss/dB	Splice Loss/dB	Total:	
Allowable Loss	1310nm	0.34dB/km	0.175	0.1	Maximum Allowable Loss Per Strand	
	1550nm	0.21dB/km	0.175	0.1		
Loss Budget	1310nm	0.04dB	0.35	0		-0.39dB
	1550nm	0.03dB	0.35	0		-0.38dB

Strand	A to B		B to A		Bi-Directional Average		Pass/Fail	Pass/Fail
	1310nm	1550nm	1310nm	1550nm	1310nm	1550nm	1310nm	1550nm
1					0.00	0.00	PASS	PASS
2					0.00	0.00	PASS	PASS
3					0.00	0.00	PASS	PASS
4					0.00	0.00	PASS	PASS
5					0.00	0.00	PASS	PASS
6					0.00	0.00	PASS	PASS
7					0.00	0.00	PASS	PASS
8					0.00	0.00	PASS	PASS
9					0.00	0.00	PASS	PASS
10					0.00	0.00	PASS	PASS
11					0.00	0.00	PASS	PASS
12					0.00	0.00	PASS	PASS
13					0.00	0.00	PASS	PASS
14					0.00	0.00	PASS	PASS
15					0.00	0.00	PASS	PASS
16					0.00	0.00	PASS	PASS
17					0.00	0.00	PASS	PASS
18					0.00	0.00	PASS	PASS
19					0.00	0.00	PASS	PASS
20					0.00	0.00	PASS	PASS
21					0.00	0.00	PASS	PASS
22					0.00	0.00	PASS	PASS
23					0.00	0.00	PASS	PASS
24					0.00	0.00	PASS	PASS

